

FULL WALL MURAL INSTALLATION INSTRUCTIONS



NOTE: MURAL IS PROVIDED WITH 2" OVERAGE (HEIGHT AND WIDTH) TO ALLOW TRIMMING IF WALLS ARE OUT OF SQUARE.

STEP ONE

Begin installation at top left. Unroll mural across the top against ceiling (requires two helpers plus person doing the stapling). Begin stapling at top left corner (**be sure that staples are no more than 1/2" from edge of mural**). As your helpers **KEEP THE MURAL PULLED TIGHT**, staple about every 12" across the top of the mural.

When you are satisfied that the mural is pulled tight without any sags or puckers, go back and staple every 2-3 inches across the top. **THE TOP MUST BE COMPLETED BEFORE CONTINUING THE INSTALLATION.**

STEP TWO

PULLING MURAL TIGHT, staple center bottom at base (**have your helper push down using the palms of their hands as you pull the mural**).

STEP THREE

PULLING MURAL TIGHT, staple left bottom corner at base (**have your helper push down using the palms of their hands as you pull the mural**). Repeat this step at right bottom corner

STEP FOUR

PULLING MURAL TIGHT, staple right center (**have your helper push using the palms of their hands as you pull the mural**). Repeat this step at left center

STEP FIVE

Go back and staple every 2-3 inches at bottom and both sides (**be sure that staples are no more than 1/2" from edge of mural**).

REMEMBER, KEEP THE MURAL PULLED TIGHT AS YOU STAPLE - THIS IS THE KEY TO A GOOD INSTALLATION!

SEE PAGE 2